KENNEDY®

Portable Air Pump
007

Thank you for ordering wireless intelligent portable air pump, making inflating easier and more convenient. This product can be used for inflating cars, motorcycles, bicycles, electric cars and balls, small inflatable toys, etc., and can also be used as tire pressure meter and flashlight.

Instructions

1. Connect one end of trachea with air pump, and install the required charging nozzle to the other end and screw into the valve core of the tire.
2. Press key "⏻" to switch on the power supply and the LCD screen and set the pressure.
3. Press key "∿" to select between four pressure units PSI, BAR, KPA, kg/cm². The LCD screen displays the air pressure value.
4. "+" and "-" are the present keys or air pressure. Set the appropriate pressure value, flashing for 3 seconds, automatic setting completed. Then press key "⏻" to start inflating.
5. The air pump will automatically stop the inflation reaches the set value.
6. Press key "SOS" for emergency rescue.
7. After inflation, unscrew one end of the trachea rapidly from the valve core first, and unscrew the other end from the air pump.
8. The original time of the air pump is about 3-5 hours.
9. The air pump is also equipped with cigarette lighter wire connect the car cigarette lighter,instruction steps as above.

Remember: The illustrations of products, accessories, user interface etc in the manual are schematic diagrams and are for reference only. Due to the update and upgrade of the product, the actual product may be slightly different from the schematic diagram. please refer to the actual product.

Warning

- Ensure correct charger is used (strong overcharge or undercharge damages the battery).
- Do not place wet skin, water, food or chemicals near the air pump.
- Keep away from open flames and high temperatures or throw into the fire to avoid explosion.
- Do not disassemble or modify the air pump.

Battery Charging:

- Connect the USB charger kit into the USB interface and connect the other end to the Type-C interface on the air pump.
- When "🔋" flashes on the air pump,the battery is being charged.
- It takes 3- 5 hours to fully charge.

Product name	Portable Digital Air Pump
Model no.	007
Inflation pressure range	0.2~10 bar/3~150psi
Working temperature	-20°C~60°C
Tolerance size	Tolerance of pressure: ±3% (including manufacturer error)
View size	1.4inch, size 11.15mm, 7 digits display
Working mode	Intermittent work (less than 1 hour)
Input parameters	7.4V,12V,1A
Charging interface	Type-C-compatible lighter power interface
Sensor accuracy	±1.5psi

Instruction Manual
ORDER CODE
KEN-503-2502K